



DX-NT400E/DX-NT430E

Two security specialists with
all the memory you need.



You know best how much memory you need for your digital time-lapse recorder. And with the DX-NT400E/DX-NT430E you choose. A removable tray is available, in which 2 internal hard drives can be installed (together max. 800 GB). The DX-NT400E/DX-NT430E conforms itself to your needs. You decide how much you record or see. Thanks to the integrated multiplexer up to 4 channels can be viewed simultaneously. And you also determine the grade of the compression and the sensor adjustment for each individual camera: with a maximum of 25 pictures per second at a resolution of 720 x 288 pixels.

The DX-NT430E has been especially designed for use in bank applications, in particular the surveillance of cash terminals. As well as recording pictures, data is also stored. A search for specific records can be carried out and the corresponding images assigned. Various search criteria can also be accessed over the recorder or the software, completing the functionality of the DX-NT430E as a total solution. A further advantage: the required protocols are pre-installed, available at no extra cost.

In critical situations too, you can rely on both the DX-NT400E/DX-NT430E. Errors during recording are automatically recognized and indicated on the monitor or over the network, allowing you to react quickly. Even in the case of a power cut, the recorders start up automatically with all preset parameters and resume recording. The integrated timer programs record in intervals or on public holidays, so that everything is under control, even when you're not there. A network connection can also be made to your recorder, at any time you wish.

- Maintenance-free operation
- Full-duplex function for simultaneous recording and playback
- Alarm recording through motion detection or alarm contact
- Fully automatic daylight saving conversion
- "On board" network connection
- Free live/playback/download/remote maintenance software Net Hunter Lite or DX-PC25



DX-NT400E/DX-NT430E

Model	DX-NT400E/DX-NT430E (Full-Duplex)
Recording System	Digital Wavelet, 720 x 288 pixels
Recording Medium	Hard drive of customer's choice
Max. Recording Capacity	2 x HDDs each 400 GB IDE
Recording Type	Field/second
Picture Recording	25 frames/second incl. motion detection
Horizontal Resolution b/w (TV Lines)	> 450
Horizontal Resolution Color (TV Lines)	> 450
No. of Video Inputs/Outputs	4/1
No. of Audio Inputs/Outputs	1/1
Audio: Recording/Continuous Playback by Run Time	Yes
On-Screen Display: Date/Time/Mode	Yes/4 modes
On-Screen Display: Alarm	Yes
On-Screen Display: Power Loss	Yes
Alarm: Time Lapse/Real Time	Yes
Alarm – Index	Yes
Alarm Recording Trigger	External alarm contact, motion detection, DX-NT430E: ATM-Cash Terminal
Recording via External Alarm Contact	Yes
No. of Timer Programs	3
HDD – Automatic Overwriting/Endless Recording	Yes
HDD Full: Acoustic Signal/Electric Contact Signal	Yes
HDD Full: Transfer to Subsequent Device	Yes
Lock Function	Yes + password
Error Indication	Yes
Continuous Recording after Power Loss	Yes
Record – Original Check: Watermark	Yes
Operating Hours Counter	Yes
Search: Fields Stepping	Yes
Search: Speeds	Yes
Search: Reverse Playback	Yes
Search: Date/Time	Yes, DX-NT430E: for ATM typical functions
Search: for Alarms	Yes/color search mode display
Automatic Summer/Winter Time	Yes
Remote Control (Cable)	Yes
Remote Control Interface	Yes (RS-232, RJ45), mode out function
Operating Voltage (Volt)	100–240 V/AC
Power Consumption (Watt)	approx. 60 W (240 V/AC)
Operating Temperature (min./max.°C)	5–40 °C
Dimensions (W x H x D)	300 x 88 x 343 mm
Weight	5.8 kg
Certification (VDE/GS/etc.)	EN 60850, EN 55022 Class B, EN 55024, EN 50130-4
Menu Languages	GB/D/FR/I/ES/RU
Items included	Wire remote control, software, operation manual, power cable
Special Features	DX-NT400E/DX-NT430E: Maintenance-free, optional removable tray, “on-board” network connection, integrated multiplexer (sequential/split function), search and find within seconds, alarm recording via motion detection and alarm contacts, 5 levels of selectable image quality (individual for each camera), audio recording (mic./line), full-duplex, digital zoom, public holiday program. Free software with live/playback/download/remote maintenance functions. DX-NT430E: with integrated ATM protocols, connects to up to 4 ATMs (with optional interface box)

(The right to make technical changes is reserved; no liability is accepted for printing or other errors)

Mitsubishi Electric Europe B. V. • German Office • Electronic Visual Systems • Gothaer Straße 8 • D-40880 Ratingen
 Tel.: +49 (0) 21 02/4 86 92 50 • Fax: +49 (0) 21 02/4 86 73 20 • www.mitsubishi-evs.de